

Specifications – RP60AU

Application Notes:

- Compact AC motor control modules for 115V AC and 230V AC motors.
- Universal mount allows for placement in many locations and allows for maximum job site flexibility. Installations could range from a single gang junction box, a location in a headrail or even large central panels that are custom built for a project.
- 60 Programmable channels: provides one-touch control of individual motors, sub-groups of motors and ALL motors.
- System programming is achieved from many different devices.
- Programmable action features include:
 - . maintained or Momentary motor action
 - . SPDT and SPST manual switch input, or X-10 control
 - . Lamp control
 - . Deadbeat feature
 - . Magnet Read Switch as an over-ride
 - . Wind features for any application
- Commands can be sent to an RP60AU from many sources. Command Sources could be:
 - . IR Remote Transmitters
 - . RF Remote Transmitters
 - . IR Key Pads
 - . RF Key Pads
 - . Standard Wall Switches (any type)

Electrical Specifications:

Input:

Line Voltage: 115AC +/- 20%
Low Voltage: Dry Contact – 0V AC

Output:

115V AC 6A 1/3 HP

Mechanical Specifications:

L: 2.6" W: 2.1" H: .875"
(L:66mm W: 53.3mm H: 22.2mm)

Typical Single Motor Schematic

